


LP 97015 (METAL SEAL)

15 mm Nominal Bore Piped Discharge Safety Relief Valve
For Liquids
PED, TÜV Approved



Pressure Range

From: 0.30 bar g. (4.35 psi g.)
To: 33.00 bar g. (478.50 psi g.)



Temperature Range

Up to: 250 °C



Flow Area

176.71 mm² (15.00 mm inlet bore diameter)



Connections

Inlet: 3/4" to 1 1/2" BSP, BSPT, NPT
Outlet: 1 1/2" BSP, NPT



Seal Materials

Nitrile
Viton®
Neoprene
Ethylene Propylene
Silicone

	LP 97015	LP 98015
1 INLET SEAT	BRASS	ST. STEEL
2 DISC	ST. STEEL 1.4401 (316)	ST. STEEL 440B
3 BALL	ST. STEEL	ST. STEEL
4 DISC HOLDER	ST. STEEL	ST. STEEL
5 PLUNGER	ST. STEEL	ST. STEEL
6 BODY	ST. STEEL	ST. STEEL
7 SPRING	ST. STEEL	ST. STEEL
8 ADJUSTER	BRASS	ST. STEEL
9 SPINDLE	ST. STEEL	ST. STEEL
10 CAP	BRASS	ST. STEEL
11 WIRE & SEAL	ST. STEEL & LEAD	ST. STEEL & LEAD
12 LEVER	BRASS	ST. STEEL
13 'O' RING	TO SUIT	TO SUIT

Notes

- Relieving pressure is set pressure +10%
- Reseating pressure is set pressure -20% (0.6 bar g. below 3.0 bar g.)
- Leak tightness at 90% set pressure to API 527
- Greater leak tightness may be achieved on request



Approvals

- TÜV Germany (AD-Merkblatt A2)
- BS EN ISO 4126-1
- PED 97/23/EC

DN15


Seetru Limited
Albion Dockside Works
Bristol BS1 6UT
England

Tel: +44 (0) 117 927 9204
Fax: +44 (0) 117 929 8193
sales@seetru.co.uk
www.seetru.co.uk



For assistance in sizing a valve to your specifications please contact the Seetru technical sales desk.

Alternate Top Fittings



DN15

Seetru Limited
Albion Dockside Works
Bristol BS1 6UT
England

Tel: +44 (0) 117 927 9204
Fax: +44 (0) 117 929 8193
sales@seetru.co.uk
www.seetru.co.uk